

Galvanised wire for sprinkler tubing



Galvanised wire suitable for installation of e.g. sprinkler pipework. Note that tension wires should always sag slightly even with the right choice of tension wire and wire tensioner.

CHARACTERISTICS

- ✓ Available in various wire gauges
- ✓ The wire is supplied as standard on reels of 25 kg
- ✓ Delivery of wire cut-to-length is also possible (No. 4 up to 15)

TECHNICAL DATA

Wire number	Wire thickness (mm)	Length/roll (m)	Weight/1000 m (kg)	Availability
4	6,0	112	222	on request
6	5,0	162	154	on request
7	4,6	191	130	on request
8	4,2	228	109	on request
9	3,8	279	89	on request
10	3,4	350	71	standard
11	3,0	451	55	standard
12	2,8	517	48	standard
13	2,4	691	36	standard
14	2,0	996	25	standard
15	1,8	1245	20	on request
16	1,6	1555	16	standard
17	1,4	2069	12	on request
18	1,2	2795	8,9	on request
19	1,0	4015	6,2	on request
20	0,9	4980	5	on request
21	0,8	6360	3,9	on request
22	0,7	8278	3	on request

INSTALLATION & MAINTENANCE

During installation, pay attention to the correct fixing of the wire with wire clamps as shown in the figure.

