

Snap-clip

Tefen



Netafim has introduced the snap-clip to clamp LDPE inline and online driplines (or with EVA) to barb connectors and barb sealings.

APPLICATION

In combination with e.g. barb connectors and grommets, for leak tight mouning of fittings in PE and driplines

CHARACTERISTICS

- ✓ Available in 6 different sizes
- ✓ Solid design
- ✓ Solid tube closing
- ✓ Reusable

TECHNICAL DATA

Material	: acetal
Maximum pressure	: 4 bar
Diameters	: 8 - 28 mm
Colour	: black
Temperature range	: -4 tot 60°C (after assembly)

INSTALLATION & MAINTENANCE

- ✓ Mount the snap-clip around the tube and squeeze the two clips tightly together. If required a small wrench may be used to gently tighten the clips even tighter.

Application

Description	Article no.	LDPE diameter and inline tubes (EVA) (mm)					
		7	10	12	16	20	25
Snap-clip 8-10	76400-011390	Fieldstand Roof sprinklers thin Suspended					
Snap-clip 11-13	76400-011450		Fieldstand Roof sprinklers thick suspended				
Snap-clip 13-15	76400-011500			Fieldstand Roof sprinklers			
Snap-clip 15-17	76400-011700				Inline tube 16 mm Dripline 16 mm		
Snap-clip 20-22	76400-012100					Inline tube 20 mm Dripline 20 mm	
Snap-clip 26-28	76400-012400						Dripline 25 mm