

# Griffon lubricant

## Griffon



Griffon offers a paste-like lubricants for the assembly of pipes, sockets and fittings with rubber ring sealed connections in drainage systems.

### CHARACTERISTICS

- ✓ Acid-free agent with Vaseline as base material
- ✓ Suitable for all diameters
- ✓ Suitable for PVC-U, ABS, PE, PP, GRP (glassfibre-reinforced plastic), concrete and coated cast iron
- ✓ Pot with 700 grams

### TECHNICAL DATA

		Lubricant
Viscosity		paste-like
Density	g/cm <sup>3</sup>	approx. 0,8
Consumption		see table
Processing temperature	°C	> 0
Storage temperature	°C	-20
Shelf life	months	24

### Consumption: Indication of number of joints per 1000 g

Diameter (mm)	90	110	125	160	200	250	315	400	500
Amount	135	90	60	45	30	20	12	8	5,5

### INSTALLATION & MAINTENANCE

#### Application conditions

1. Cut off the pipe at right angles, chamfer and deburr the ends
  2. Remove any soiling and moisture
  3. Apply lubricants to the pipe end and the rubber sleeve
  4. Assemble the joint immediately by pushing the pipe into the sleeve up to the stop
- ✓ The joint can be easily adjusted
  - ✓ Close package tightly immediately after use
  - ✓ Spots and residues can be removed using a degreasing agent