

Wire hooks



Netafim offers various hanger hooks to support tension wire and various pipes, including rain pipes, main pipe and semi-pipes.

IRRIGATION PIPE HOOKS

- ✓ Galvanised wire, 2.8 mm dia.
- ✓ Standard for pipe diameter 32 mm (for 25 and 40 mm on request)
- ✓ Also available for attachment to a 51 mm heater pipe
Installation spacing for sprinkler pipe +/- 75 cm
- ✓ Supplied in packs of 100 hooks
- ✓ Also available as heater hooks (2 models)

(DOUBLE) WIRE SUSPENSION HOOKS

- ✓ Wire suspension hooks are made-to-measured from galvanised wire of 2.8 mm or 4.0 mm diameter
- ✓ When ordering, indicate the width of the beam, the length of the hook (top of truss to underside of pipe) and the diameter of the pipe (in mm).
This information can best be provided in a sketch

J-TRUSS HOOK

- ✓ Used for the installation of PVC (main) lines from 63 to 125 mm
- ✓ Produced made-to-measure from galvanised steel strip 25 x 3 mm

DOUBLE J TRUSS HOOK

- ✓ Double hook for main and semi line so that a pipe can be installed on both sides of the truss
- ✓ Produced made-to-measure from galvanised steel strip with various thicknesses and widths, depending on the pipe diameter
- ✓ Used for the installation of (semi) lines from 40 to 63mm

