

# Swing Joint

## Tavlit / Hunter



The Swing Joint is used to easily position a pop-up sprinkler parallel to the ground and is therefore extremely suitable for compensating differences in height between the ground and the depth of the pipework.

The Swing Joint is available in various versions.

### APPLICATION

Garden and park irrigation

### TECHNICAL DATA

	<b>Tavlit</b>	<b>Hunter</b>
Max. pressure	: 4 bar	: 10 bar
Material	: PP	: PP
No. of hinge points	: 4	: 2
Connection	: ½" / ¾" BSPT	: ½" / ¾" BSPT ext
Length	: 150 mm	: 300 mm
Size	: ½" 13 mm	: ½" en ¾" 12,5 mm
To be combined with	: self-seal and swivel fittings	: n/a

# Protection box



Protection boxes are used to safely store underground products such as valves, flushing valves, air/vacuum breaker valves and to protect them from external influences.

### APPLICATION

Irrigation systems, sprinkler installations for horse stables

### CHARACTERISTICS

- ✓ Available in 4 versions: Mini, Large, Standard and Jumbo
- ✓ Equipped with a green cover (partly lockable)
- ✓ Connect two boxes together to double the height

### TECHNICAL DATA

Version	Dimensions* (mm)			Maximum load (kg)	Weight (kg)
	Lower base	Upper base	Height		
Mini	200	160	230	250	0,49
Large	320	225	250	450	1,23
Standard	380x496	273x405	300	700	3,66
Jumbo	500x640	370x520	300	1000	7,18

\* The dimensions shown are from the outside of the protective box. Please note: in the past protective boxes were supplied with different dimensions.